



STANDARD 8'-0" SECTION:

1. ATTACH TOP RAIL AND MID RAIL TO ONE END POST. HAND TIGHTEN SETSCREWS.
2. ATTACH OTHER END POST TO TOP RAIL AND MID RAIL. HAND TIGHTEN SETSCREWS.
3. LOCATE RAIL ASSEMBLY AND ANCHOR INTO POSITION. ANCHORS NOT PROVIDED.
4. USING A LEVEL, CHECK THAT POST ARE VERTICAL AND RAILS ARE LEVEL.
5. TIGHTEN ALL SETSCREWS.

THIS DRAWING AND ALL THE INFORMATION THEREON IS THE PROPERTY OF THE HOLLANDER MFG. CO., IS CONFIDENTIAL AND MUST NOT BE MADE PUBLIC, NOR COPIED, NOR USED, TO THE DISADVANTAGE OF SAID HOLLANDER MFG. CO. AND IS SUBJECT TO RETURN ON DEMAND.
 COPYRIGHT 2013.
 HOLLANDER - MANUFACTURING CO.

NO.	REVISIONS	DATE	APPROVED
0	RELEASED FOR APPROVAL	1-15-13	BW

Hollander[®]
 STRUCTURAL ENGINEERING GROUP
 10285 WAYNE AVENUE
 CINCINNATI, OH 45215-6399
 PHONE: (800) 772-8800 FAX: (502) 772-8806
 WWW.HOLLANDER.COM

PROJECT	CUSTOMER	DESCRIPTION
STRAIGHT RAIL SECTION 8'-0" c/c POST 42" HIGH RAIL		BUMBLE BEE RAIL SECTION DRAWINGS

PROJECT NO.	DATE	REVISED BY
50241	1-15-12	NTS

DESCRIPTION	QUANTITY	UNIT
POWDER COAT		
STL. PIPE/ALUM FITTING	1	1

DRW. NO.	APP. BY	DATE
GG	BW	1-15-12

